

**LED**  
Downlight

# TILTABLE DOWNLIGHT

Energy-Efficient integrated LED tiltable downlight.



<b>30000</b> Hours	<b>45°</b> Beam Angle
<b>68mm</b> Cutout	Tiltable
Dimmable	Easy Installation
Non Dimmable	Easy Installation
<b>5</b> YEAR Warranty	<b>IP44</b>



Loop-in Loop-out terminal

### Specification


Voltage 220-240V~  
50/60Hz

Ambient Temp -20°C to 45°C

### Colour Temp

3000K 4000K 6500K

### Dimensions



### Available Colours:



White



Brushed Nickel



Chrome

Energy Class: **F** A G

Order Code	Bezel Colour	Wattage	Dimmable	CCT**	Lumen*	Dimensions (A x B mm)	Qty/CTN
15451	White	4.8W	No	Switchable	500lm	ø87x47	48
15468	Brushed Nickel	4.8W	No	Switchable	500lm	ø87x47	48
15475	Chrome	4.8W	No	Switchable	500lm	ø87x47	48

Energy Class: **G** A G

Order Code	Bezel Colour	Wattage	Dimmable	CCT**	Lumen*	Dimensions (A x B mm)	Qty/CTN
15482	White	6W	Yes	Switchable	570lm	ø87x47	48
15499	Brushed Nickel	6W	Yes	Switchable	570lm	ø87x47	48
15505	Chrome	6W	Yes	Switchable	570lm	ø87x47	48

\*at 4000K

\*\*When CCT switchable, colour temperature switches between 3000K, 4000K & 6500K

